



# Aprisa LTE

## SMART, SECURE LTE CELLULAR ROUTER

[DATASHEET \[ETS\]](#)

Smart, secure, industry-leading performance 3GPP LTE communications for critical infrastructure monitoring and control for the electricity, water, oil and gas industries. Hardened LTE for both mission and business critical applications with enhanced broadband data rates and reduced latency.

- **Secure:** with its vetted defense in depth approach, including AES encryption, strict authentication, L2 / L3 filtering, GRE, IPSec, and DMVPN support, the Aprisa LTE protects against vulnerabilities and malicious attacks.
- **Interfaces:** the Aprisa LTE supports serial and Ethernet with SFP support for additional electrical and optical connections in a single, compact form factor.
- **Adaptable:** the Aprisa LTE integrates into a wide range of industrial and utility applications with redundant carrier connections for public and private networks. The Aprisa Power Control (APC) feature delivers ultra-low power sleep mode for solar applications.
- **Advanced mobility and Wi-Fi:** supports advanced remote visibility in vehicle networks with GNSS location / navigation service and 2x2 MIMO Wi-Fi AP/client mode for workforce mobility communication.
- **Advanced L2 / L3 capabilities:** selectable L2 or L3 modes with VLAN, QoS, NAT, IPv4, and IPv6 transition support to maximize performance and prioritize mission critical traffic while meeting tough security and IP network policy imperatives.
- **Reliable and robust:** the Aprisa LTE requires no manual component tuning and maintains its performance over a wide temperature range using full specification industrially rated components and shared Aprisa family heritage.
- **Easily managed:** an easy to use GUI supports local element management via HTTPS or via CLI with remote element management over the air via SNMP and NETCONF support to allow network-wide monitoring, control, and orchestration via a variety of supported third party network management systems.
- **Failover:** single radio, dual SIM with switch over, and interface failover to provide alternate path routing on WAN or FAN failure.

### Applications

- **Electricity grid:** distribution automation, control and protection
- **Smart grid:** DA, DFA, cap bank control
- **Smart cities:** traffic control, video surveillance
- **Oil & gas:** production metering, lift pump automation
- **AMI / AMR:** high density data concentrator backhaul
- **Renewables:** DER, solar and wind farms, hydro automation
- **Water and wastewater:** flow, level, pump, and valve automation
- **Public safety, utility, mining:** fleet management, vehicle tracking, workforce mobility

# Aprisa LTE

## SMART, SECURE LTE CELLULAR ROUTER

DATASHEET [ETSI]



## Specifications

General	
Network Integration	LTE, Wi-Fi, Serial, Ethernet, bridge and router on a per port basis
Protocols	
Ethernet	IEEE 802.3, 802.1d/q/p, VLAN, STP, ARP Ethernet 10/100/1000BASE-T and 100/1000Base-X
Serial	RS-232 / RS-422 / RS-485, and Terminal Server support
VPN	IPsec, GRE, mGRE, and DMVPN
Routing	BGP / MP-BGP, OSPF, EIGRP, NHRP, VRF, RIPv1/v2, IPv4 / IPv6, static, and IP-SLA
IPv4 / IPv6 SERVICES	VLAN L3 interface, DHCP server / client, DNS, DDNS, and NAT
QoS	Hierarchical QoS, cellular TFT / QCI, classification (L2-L4), ingress policing with two rate three colour marking, shaping, priority assignment, strict priority, fair queue, and prioritised schedulers
LTE 4G and NR 5G	
LTE <sup>[2]</sup>	Downlink LTE Cat-6 (300 / 50 Mbps) / Cat-12 (600 / 150 Mbps) Uplink LTE Cat-6 / 7 / 12 / 13
LTE Band Options Support <sup>[1]</sup>	B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B14, B17, B18, B19, B20, B21, B25, B26, B28, B29, B30, B32, B38, B39, B40, B41, B42, B43, B46, B48, and B66
SIM	Dual Micro SIM
GNSS	
Positioning and Timing	GPS, GLONASS, Beidou, Galileo, and QZSS (option)
Max Channels	30 (16 GPS, 14 GLONASS) simultaneous tracking
Protocol	NMEA 0183 V3.0
Wi-Fi	
Standards (2.4 / 5 GHz)	IEEE 802.11 a/b/g/n 2x2 MIMO / IEEE 802.11 n/ac 2x2 MIMO
Frequency Range	2.4 to 2.495 GHz, 5.15 to 5.825 GHz
Channel (2.4 / 5 GHz)	2.4 GHz (20 / 40 MHz) / 5 GHz (20 / 40 / 80 MHz)
Performance	Up to 866.7 Mbps
Security	WPA / WPA2 / WPA3 Personal / Enterprise, WEP / TKIP, AES-CCMP, 802.1x
Modes	Access Point, Client and Access Point / Client

# Aprisa LTE

## SMART, SECURE LTE CELLULAR ROUTER

DATASHEET [ETSI]



Security	
Firewall	Stateful firewall, zone-based policy, VRF-aware, dynamic, and static
Symmetric Encryption	3DES AES 128, 192, or 256 CBC / CTR / CCM8-CCM16 / GCM8-GCM16
Authentication	MD5 / SHA-1 / SHA-256 / SHA-384 / SHA-512
DH group	DH-1 / DH-2 / DH-5 / DH-14 / DH-15 / DH-16 / DH-19 / DH-20 / DH-21
IKE	IKEv1 and IKEv2 (authentication via PSK or certificate) PFS option
FIPS	FIPS 197 (AES) and FIPS 140-2: Security Requirements
Hardening	NIST SCAP, IDS, processes monitoring
Tamper	MEMS high-performance 3-axis accelerometer

Interfaces	
Ethernet Ports	2 ports RJ45 IEEE 802.3, 802.1d/q/p
Serial Ports	1 port RJ45 RS-232 / RS-422 / RS-485, 300 - 230,400 bit/s
SFP	1 port Small Form-factor Pluggable (SFP) supporting both optical and copper SFP modules
Management	1 port USB-C rotationally-symmetric
Antennas	Cellular Main and Cellular Diversity QMA 50 ohm female GNSS QMA 50 ohm female <sup>[3]</sup> Wi-Fi Ant 1 (main), Ant 2 (diversity) QMA 50 ohm female
I/O Pins	1 input pin and 1 output pin (on power supply connector)
LEDs	Status: OK, AUX Diagnostics: SFP, TX, RX and Wi-Fi Ethernet / Serial Ports: Active and Link

Power				
Input Voltage	9 to 32 VDC negative earth			
Sleep Power	< 0.04 W			
Standby Power <small>(no Wi-fi, no USB-C, no I/O)</small>	< 3.6 W			
Typical Power	3.6 W to 5.7 W			
Element Maximum Power	USB-C accessories	<4.5 W	Wi-Fi	<1.5 W
	I/O	<2.0 W	GPS Bias	<0.3 W
	SFP	<1.0 W	LTE and CPU both at 100%	<5.7 W

Mechanical	
Dimensions (not including connectors)	177 mm (W) x 110 mm (D) x 41.5 mm (H) 6.97" (W) x 4.33" (D) x 1.63" (H)
Weight	740 g (1.67 lbs)
Mounting	Wall, Rack or DIN rail

# Aprisa LTE

## SMART, SECURE LTE CELLULAR ROUTER

DATASHEET [ETSI]



Environmental	
Operating Temperature	-30 to +70 °C (-22 to +158 °F)
Storage Temperature	-40 to +85 °C (-40 to +185 °F)
Humidity	Maximum 95 % non-condensing
Management & Diagnostics	
Local Management	SSH and HTTP/S web servers with full control / diagnostics Software upgrade via HTTPS / SFTP from PC or management system
Network Management	SNMPv3 and TRAP security support for integration with external network management systems
Orchestration	NETCONF (RFC 6241) <sup>[4]</sup>
Compliance	
LTE	EU CE Mark ETSI EN 301 908-1 EN 301 908-13 Australia Regulatory Compliance Mark (RCM) New Zealand R-NZ
Wi-Fi	2.4 GHz EN 300 328 5 GHz EN 301 893
EMC	EN 301 489-1, , EN 301 489-52
Safety	EN / UL / IEC 62368-1, CB Certified, UL Listed
Hazardous Location	Class 1 division 2, Groups ABCD for hazardous locations
Environmental	Substation hardened ETSI EN 300 019-2-3 Ingress Protection IP41
Electric Substation	IEEE 1613 Class 2 and IEC 61850-3
Vehicle	ISO 7637-2, ISO 16750-2 (12V Code D 24V Code E) Shock & Vibration: SAE J1455

**Notes:**

- [1] Band availability model dependent
- [2] Uplink / downlink UE Category model dependent
- [3] DC bias present on this connector (switchable) for active GPS antenna operation
- [4] Please consult Aviat Networks for availability. 5G compliance pending.
- [5] 1,000 hours of continuous operation at this temperature independently tested by Bureau Veritas



## Disclaimer

This material is for informational purposes only and does not constitute a legal obligation to deliver any product, feature or functionality and should not be relied upon in making purchasing decisions. All specifications are subject to change without notice. The development, release and timing of any features or functionality described for our products is at Aviat Networks' sole discretion.

For details of availability, Please contact your Aviat Networks Sales Representative.

LTE is a trademark of ETSI, used with permission for Aprisa products containing LTE functionality.  
USB-C is a trademark of the USB Implementers Forum.

Aviat, Aviat Networks and the Aviat logo are trademarks or registered trademarks of Aviat Networks, Inc.  
Copyright © Aviat Networks, Inc. [2024] All Rights Reserved. Data subject to change without notice.