



Aviat
NETWORKS

Aprisa SR+

SMART, SECURE POINT-TO-MULTIPOINT RADIO
VHF, 220 MHz, and UHF licensed bands

[DATASHEET \[ETSII\]](#)



Smart, secure, industry-leading speed licensed point-to-multipoint SCADA communications for industrial monitoring and control for the electricity, water, oil and gas industries – now with 256 QAM

- **High capacity:** to meet the growing number of data-intensive applications in the SCADA environment, the Aprisa SR+ provides data rates of up to 512 kbit/s half duplex / 1,024 kbit/s full duplex in 100 kHz licensed channels.
- **Secure:** with its defense in depth approach, including AES encryption, authentication, address filtering and user access control including RADIUS, the Aprisa SR+ protects against vulnerabilities and malicious attacks.
- **Future-proof:** the Aprisa SR+ supports dual serial and dual Ethernet ports in a single, compact form factor, designed to cryptographically secure legacy serial, protect existing device investment, and enable new applications. Old and new application protocols can be run side by side.
- **Advanced L2 / L3 capabilities:** selectable L2 bridge, L3 router, or advanced gateway router combination L2 / L3 modes with VLAN, QoS, NAT, and filtering attributes to maximize capacity in constrained bandwidth and prioritize mission critical traffic while meeting tough security and IP network policy imperatives.
- **Adaptable:** the Aprisa SR+ integrates into a range of network topologies, with each unit configurable as a master station, repeater or remote station; connect multiple RTUs / PLCs to a single radio.
- **Flexible interfaces:** the data interfaces can be configured for serial or Ethernet operation; a range of options are supported, including two serial and two Ethernet, one serial and three Ethernet, or four Ethernet ports. Support for NMEA GPS receiver option.
- **Link efficiency:** Adaptive Coding and Modulation (ACM) and forward error correction maintains the integrity of the wireless connection while an effective channel access scheme and IP routing ensures efficient transfer of data across the Aprisa SR+ network. Automatic Transmit Power Control maintains the minimum transmit power required for effective communications enhancing both frequency reuse and power savings. Advanced payload and Ethernet / IP / TCP / UDP header compression.
- **Reliable and robust:** the Aprisa SR+ requires no manual component tuning and maintains its performance over a wide temperature range using full specification industrially rated components and shared Aprisa family heritage.
- **Easily managed:** an easy to use GUI supports local element management via HTTPS and remote element management over the air and SNMP support allows network-wide monitoring and control via a variety of supported third party network management systems.

Applications

- **Electricity grid:** distribution automation control and protection in MV / HV distribution / transmission
- **Smart grid, DA, DFA, DER, cap bank control Oil & Gas:** production metering, lift pump automation
- **AMI / AMR:** high density data concentrator backhaul
- **Renewables:** wind farm, tidal, hydro automation
- **Water and wastewater:** flow, level, pressure modulation automation and pump status

Aprisa SR+

SMART, SECURE POINT-TO-MULTIPOINT RADIO

DATASHEET [ETSI] VHF, 220 MHz, AND UHF LICENSED BANDS



Specifications

General	
Network Topology	Point-To-MultiPoint (PTMP), Base, Remote, Repeater Point-To-Point (PTP) FD see 'Aprisa SR+ PTP Datasheet'
Network Integration	Serial and Ethernet (router or bridge mode)

Protocols	
Ethernet	IEEE 802.3, 802.1d/q/p
Serial	Legacy RS-232 transport, Mirrored Bits ®, SLIP and Terminal Server support
Wireless	Proprietary
SCADA	Transparent to all common SCADA protocols such as Modbus, IEC 60870-5-101/104, DNP3 or similar

Radio	Frequency Band (MHz)	Tuning Range (MHz)	Tune Step (kHz)
Frequency Range	135	135 – 175	0.625
	220 ^[2]	215 – 240 ^[2]	0.625 ^[2]
	320	320 – 400	6.25
	400	400 – 470	1.25
	450	450 – 520	6.25
Channel Size	12.5 kHz, 20 kHz, 25 kHz, 50 kHz and 100 kHz ^[2] software selectable		
Duplex	Single frequency half-duplex Dual frequency half-duplex Dual frequency full-duplex		
Frequency Stability	± 0.5 ppm		
Frequency Aging	< 1 ppm / annum		

Transmitter	
Max Peak Envelope Power (PEP)	10.0 W (+40 dBm)
Average Power Output	256 QAM 0.01 – 2.0 W (+10 to +33 dBm, in 1 dB steps)
	64 QAM 0.01 – 2.5 W (+10 to +34 dBm, in 1 dB steps)
	16 QAM 0.01 – 3.2 W (+10 to +35 dBm, in 1 dB steps)
	QPSK 0.01 – 5.0 W (+10 to +37 dBm, in 1 dB steps)
	4-CPFSK 0.01 – 10.0 W (+10 to +40 dBm, in 1 dB steps) ^[2]
Adjacent Channel Power	< -60 dBc
Transient Adjacent Channel Power	< -60 dBc
Spurious Emissions	< -37 dBm
Attack Time	< 1.5 ms
Release Time	< 0.5 ms
Data Turnaround Time	< 2 ms
Emission Designator	Contact Aviat Networks for Emission Reports.

Aprisa SR+

SMART, SECURE POINT-TO-MULTIPOINT RADIO

DATASHEET [ETSI] VHF, 220 MHz, AND UHF LICENSED BANDS



Receiver			12.5 kHz	20 kHz	25 kHz	50 kHz	100 kHz
Sensitivity (BER < 10 ⁻⁶)	min coded	256 QAM	-95 dBm	-91 dBm	-91 dBm	-88 dBm	-85 dBm
	max coded	64 QAM	-103 dBm	-99 dBm	-99 dBm	-96 dBm	-93 dBm
	max coded	16 QAM	-110 dBm	-107 dBm	-107 dBm	-104 dBm	-101 dBm
	max coded	QPSK	-115 dBm	-112 dBm	-112 dBm	-109 dBm	-106 dBm
	min coded	4-QPSK	-113 dBm	-110 dBm	-110 dBm	-107 dBm	-104 dBm
Adjacent Channel Selectivity			>-47 dBm	>-37 dBm	>-37 dBm	>-37 dBm	>-37 dBm
		^[1]	[>48 dB]	[>58 dB]	[>58 dB]	[>58 dB]	[>58 dB]
Co-Channel Rejection	max coded	QPSK	>-10 dB				
Co-Channel Rejection	min coded	256 QAM	>-26 dB				
Intermodulation Response Rejection			>-35 dBm [>60 dB ^[1]]				
Blocking or Desensitisation			>-17 dBm [>78 dB ^[1]]				
Spurious Response Rejection			>-32 dBm [>63 dB ^[1]]				

Modem		12.5 kHz	20 kHz	25 kHz	50 kHz	100 kHz
Gross Data Rate	256 QAM	80 kbit/s	112 kbit/s	160 kbit/s	288 kbit/s	512 kbit/s
	64 QAM	60 kbit/s	84 kbit/s	120 kbit/s	216 kbit/s	384 kbit/s
	16 QAM	40 kbit/s	56 kbit/s	80 kbit/s	144 kbit/s	256 kbit/s
	QPSK	20 kbit/s	28 kbit/s	40 kbit/s	72 kbit/s	128 kbit/s
	4-QPSK	9.6 kbit/s	9.6 kbit/s	19.2 kbit/s	38.4 kbit/s	76.8 kbit/s
Forward Error Correction	Variable length concatenated Reed Solomon plus convolutional code					
Adaptive Burst Support	Adaptive Coding and Modulation					

Security	
Data Encryption	256, 192 or 128 bit AES
Data Authentication	CCM
Cryptographic Protection	FIPS 140-2
IPSEC	Transparent

Interfaces	
Ethernet Ports	RJ45 10/100Base-T auto-neg MDI/MDIX
Serial Ports	RJ45 RS-232 Additional RS-232 / RS-485 port via USB converter (optional)
GPS Receiver	Support for optional USP connect GPS receiver
Management	1 x USB micro type B (device port) 1 x USB standard type A (host port) 1 x Alarm port RJ45
Antenna	2 x TNC 50 ohm female Software selectable single or dual port operation
LEDs	Status: OK, MODE, AUX, TX, RX Diagnostics: RSSI, traffic port status
Test Button	Toggles LEDs between diagnostics / status

Aprisa SR+

SMART, SECURE POINT-TO-MULTIPOINT RADIO

DATASHEET [ETSI] VHF, 220 MHz, AND UHF LICENSED BANDS



Product Options (specified at order)		
Data Port Configuration Options	2 x Ethernet ports + 2 serial ports 3 x Ethernet ports + 1 serial port 4 x Ethernet ports	
Duplex Options	Half Duplex or Full Duplex	
Protected Station Options	Providing hot-swappable / hot-standby redundant hardware switching	
Power		
Input Voltage	Radio	10 – 30 VDC negative earth
	Protected Station	10 – 60 VDC floating
Receive	All bands except 320 MHz	< 3 W in active receive state < 2 W in idle receive state, < 0.5 W in sleep mode
	320 MHz	< 7 W
Transmit	135 and 220 MHz	< 26 W
	400 and 450 MHz	< 28 W
	320 MHz	< 35 W
Mechanical		
Dimensions (not including connectors)	Radio	210 mm (W) x 130 mm (D) x 41.5 mm (H) 8.27" (W) x 5.12" (D) x 1.63" (H)
	Protected Station	434 mm (W) x 372 mm (D) x 88.9 mm (H) 2 RU 17.1" (W) 14.6" (D) 3.5" (H)
Weight	Radio	1.25 kg (2.81 lbs)
	Protected Station	10.0 kg (22 lbs) (includes the 2 radios)
Mounting	Wall, Rack or DIN rail (radio only)	
Environmental		
Operating Temperature	-40 to +70 °C	
Humidity	Maximum 95 % non-condensing	
Management & Diagnostics		
Local Management	SSH and HTTP/S web servers with full control / diagnostics Partial diagnostics via LEDs and test button Software upgrade from PC or USB flash drive	
Remote Element	SSH and HTTP/S over-the-air remote element management with control / diagnostics Network software upgrade over-the-air	
Network	SNMPv2 and SNMPv3 security support for integration with external network management systems	
Over the Air	Low overhead SuperVisor Extended NetworkManagement (EXM)	

Aprisa SR+

SMART, SECURE POINT-TO-MULTIPOINT RADIO

DATASHEET [ETSI] VHF, 220 MHz, AND UHF LICENSED BANDS



Compliance		
RED Compliance		Tested in accordance with the Radio Equipment Directive 2014/53/EU ^[3]
RF	12.5 kHz	EN 300 113
	25 kHz, 50 kHz and 100 kHz	EN 302 561 ^[4]
EMC		EN 301 489-1 and 5
Safety		1EN/UL/IEC 62368-1, CB Certified, UL listed
Hazardous Location		Class 1 division 2 for hazardous locations
Environmental		ETS 300 019 Class 3.4, Ingress Protection IP51 Substation hardened to IEEE 1613 class 2 and IEC 61850-3
Electric Substation		IEEE 1613 Class 2 and IEC 61850-3

Notes:

[1] The receiver figures are shown in typical fixed interference dBm values and dB values [in brackets] relative to the sensitivity. Relative values are given for QPSK modulation and max coded FEC. Refer to the Aprisa SR+ User Manual for a complete list of modulation and coding levels.

[2] Please consult Aviat Networks for availability

[3] 100 kHz subject to EU RED verification

[4] 50 kHz, RX compliance to 64 QAM

Disclaimer

This material is for informational purposes only and does not constitute a legal obligation to deliver any product, feature or functionality and should not be relied upon in making purchasing decisions. All specifications are subject to change without notice. The development, release and timing of any features or functionality described for our products is at Aviat Networks' sole discretion.

For details of availability, Please contact your Aviat Networks Sales Representative.

Aviat, Aviat Networks and the Aviat logo are trademarks or registered trademarks of Aviat Networks, Inc.
Copyright © Aviat Networks, Inc. [2024] All Rights Reserved. Data subject to change without notice.